

Mobile Emergency Response Platform

This application is a continuation-in-part of non-provisional Patent Application No. 09/574,888 filed on May 19, 2000, which is incorporated herein by reference.

5 Background

Emergency situations can arise in remote areas that are not accessible by roads or pathways. Such emergency situations can include activities surrounding the rescue and retrieval of downed aircraft, forest fires, natural disasters, rural terrorist attacks, coordinated searches for lost or missing persons, rural manhunts, and accidental ecological poisonings which can include
10 nuclear, chemical, or biological discharges. However, due to the remoteness of a given location, it may be necessary that multiple emergency response parties be deployed over a large geographic area. For effective coordination of such efforts, it is crucial that each party be enabled to maintain communications with a central command center and/or with each other.

Individual response parties can range from single individuals on foot to additional
15 response vehicles and aircraft. Some situations may also involve different types of emergency response services from different areas of the country. Consequently, the communications and response equipment carried by each party can vary greatly and be incompatible with those of other parties. In some circumstances, effective emergency response may require the addition of administration or expertise by personnel that are located tens, hundreds, or even thousands of
20 miles away from the location of the emergency situation. However, response parties that are on foot may be limited by the fact that hand held communication equipment can be of limited range.

As response parties enter and remain present in the field, their ability to perform emergency operations often depends upon both observable and non-observable environmental conditions. Such environmental conditions can include natural factors such as barometric

pressure, wind velocity and temperature as well as man-made factors such as the presence of radioactive fallout and chemical and biological agents. It can be crucial for in-field personnel to remain informed about current and changing environmental conditions, though it may be impractical or impossible for personnel to carry the necessary measuring instrumentation into the field with them. In the case of firefighting, for example, the fire fighters need to constantly be aware of wind velocities. If winds shift, for example, the angle of attack and strategy for fighting a fire may have to be changed. Thus, personnel may have to rely on their wireless communication devices to receive environmental information as it is measured from a remote location.

Command, communication linking, and environmental monitoring operations may have to be conducted at a location that is physically in or near the field of the emergency situation. Given range limits on the personal communication devices of response parties and the advantages of taking environmental measurements in the vicinity of the emergency situation, a platform for conducting emergency response command operations must often be able penetrate deep into even the most inaccessible or remote locations when an emergency situation erupts there. Such locations may be separated from the nearest road, trail, or pathway by great distances and by various terrains that can include sand, mud, snow, ice, deep water, swamps, thickly wooded areas, grasslands, man made debris and obstacles such as stairways, concrete, sharp metal, and glass, and terrains exhibiting extreme vertical angles. Thus, an effective platform for quickly responding to such remote emergencies must be able to move across multiple different types of off-road environments without modification immediately preceding or during an emergency operation.

Previous attempts to integrate command, communication, and environmental monitoring operations during an emergency situation based in aircraft or at fixed locations have been limited

by the inability of coordinators and administrators to get to the scene of the crisis so as to provide on-the-spot command with a knowledge of the environmental conditions of the incident. From a remote location, direct environmental measurements may not be possible. The high speed of aircraft and the distances of fixed command centers from the vicinity of the emergency situation can also make it difficult or impossible for in-field response parties to use their personal communication equipment to correspond with such command centers. Attempts to integrate such command centers using a base vehicle such as a tractor trailer, four-wheel or truck-style of vehicle have been limited since none of these vehicles can be used to traverse off-trail areas that are heavily wooded, full of the thickest swamps, mud, ice, or snow, or that require the crossing of deep waterways, i.e. amphibious operation.

Simply recognizing that it is important to coordinate among multiple parties and vehicles that are involved in an emergency response operation does not itself dictate the choice of platform for the coordinating function or the choice of information and presentation format. Thus, there remains a need for a way to control, coordinate, and administer the various parties that are involved in an emergency response operation that is conducted in a remote or inaccessible area.

Summary

The invention is a mobile emergency response platform for monitoring and conducting in-field administration and coordination of emergency response activities. The platform is based on an all-terrain vehicle of the type that can accommodate at least two persons and is driven by tracks such as tank tracks, at least six wheels, or a combination of both wheels and tracks. The all-terrain vehicle has the capability, without requiring in-field modification by an operator, of traversing multiple off-road surfaces that include, at minimum, each of sand, mud, snow,

swampland, thickly wooded areas, ice, grasslands, man-made rubble and debris, surfaces having angles of about at least thirty degrees from horizontal, and the floatable operation of the vehicle on waterways. Thus, the vehicle can be driven directly from any one type of these terrains to any other type of these terrains without requiring alterations to the configuration of the vehicle.

5 The vehicle is equipped with a suite of electronic communication equipment that is capable of being moved with the platform across each off-road surface to a first remote location that is ideally in the vicinity of the emergency situation for optimal in-field command. The communication equipment is configured to have the capability of receiving, while being located at the first remote location, at least two types of wireless communication transmissions from one
10 or more second remote locations, which are generally the positions of in-field response personnel, aircraft, or other remotely positioned command or information centers. While the platform is located at the first remote location, the platform is also capable of transmitting at least two types of wireless communication transmissions to each second remote location.

 The electronic communication equipment has the additional capability, while the
15 platform is located in the field at the first remote location, of performing a crossover operation in which an incoming signal of a first signal type is received, regenerated, possibly amplified, and relayed as a second signal type that is different from the first signal type. This crossover operation is two-way in that the electronic communication equipment can also receive an incoming signal of the second signal type and regenerate and relay the signal as a signal of the
20 first signal type.

 In-field environmental measurements are taken with an environmental monitoring station that is included and capable of being moved across the multiple off-road surfaces with the platform to the in-field first remote location. The environmental monitoring station is capable of taking in-field measurements of environmental conditions surrounding said platform, which are

normally the environmental conditions of the area of the emergency. Most embodiments of the invention are configured to allow information about the in-field measurements taken by the environmental monitoring station to be transmitted to each second remote location in at least one of the first or second signal types.

5 Some embodiments of the invention include electronic positioning equipment as part of the platform on the all-terrain vehicle. The positioning equipment is capable of providing, at any given in-field first remote location, information about the position of the mobile platform. The electronic positioning equipment can use any one of a number of wireless technologies, having satellite, radio, mechanical, or hybrid-based position-measuring devices incorporated therein.

10 The electronic communication equipment is often configured to also allow information about the position of the platform at a given first remote location to be transmitted directly to one or more second remote locations in at least one of the first or second signal types.

Those skilled in the art will realize that this invention is capable of embodiments which are different from those shown and that details of the structure of the mobile platform can be

15 changed in various manners without departing from the scope of the invention. Accordingly, the drawings and descriptions are to be regarded as including such equivalent mobile platforms as do not depart from the spirit and scope of the invention.

Brief Description of the Drawings

20 For a more complete understanding and appreciation of this invention and many of its advantages, reference should be made to the following, detailed description taken in conjunction with the accompanying drawings wherein:

FIG. 1 is a rear perspective view of a mobile emergency response platform according to one embodiment of the invention;

FIG. 2 is an operator's view of a vehicle dashboard of the platform of FIG. 1 depicting an example suite of wireless technologies according to one embodiment of the invention;

FIG. 3 is a topographic diagram depicting an example emergency situation in which a platform of the invention is utilized to administer, coordinate and command the activities of multiple in-field emergency response personnel;

FIG. 4 is a front perspective view of a mobile emergency response platform according to one embodiment of the invention;

FIG. 5 is an operator's view of a vehicle dashboard of the platform of FIG. 4 depicting an example suite of wireless technologies according to one embodiment of the invention;

FIG. 6 is a top view of the rear portion of the platform of FIG. 4 having the seat of the passenger area lifted to reveal concealed electronic communications equipment;

FIG. 7 is a front perspective view of a mobile emergency response platform according to one embodiment of the invention; and

FIG. 8 is a rear perspective view of a mobile emergency response platform according to one embodiment of the invention.

Detailed Description

Referring to the drawings, identical reference numerals are used to designate the same or corresponding parts throughout the several embodiments and figures shown and described. In some figures, some specific embodiment variations in corresponding parts are denoted with the addition of lower case letters to reference numerals.

FIG. 1 depicts an all-terrain vehicle **10a** that is the basis for an embodiment of a mobile platform **11a** according to the invention. The all-terrain vehicle **10a** is of the type having six, eight, or more wheels **13**, with suitable vehicles including the Argo and Centaur All-Terrain

Vehicles, both being available from Ontario Drive & Gear Limited of New Hamburg, Ontario, Canada, and the Max and Buffalo All-Terrain Vehicles, both being available from Recreatives Industries, Inc. of Buffalo, New York. Some embodiments may be outfitted with tracks or a combination of tracks and wheels or have additional features as described below. Tires **21** used on the vehicle are formed to provide traction on slippery ground. The wheels **13** are spaced substantially equidistant from each other in order to enhance traction and off-road operation. FIG. 4 depicts a platform **11b** based on a similar vehicle **10b** having tracks **15** that are positioned over wheels **13** to increase traction and reduce downward pressure of the vehicle **10b**. The tracks **15** are usually removable to allow for the vehicle **10b** to operate with wheels **13** alone. In construction, the tracks **15** can be comprised of metal, rubber, or a synthetic material. The tracks **15** can also be cleated to allow for optimal travel over snow and marsh areas.

Referring again to FIG. 1, the vehicle **10a** is relatively lightweight, usually weighing no more than approximately 1100 to 3000 pounds and may exert a downward pressure of less than about three to four pounds per square inch when operated only with wheels **13** or less than about one pound per square inch when operated with tracks, such as the tracks **15** shown on the platform **11b** in FIG.4. Referring again to FIG. 1, the vehicle **10a** typically includes a two or four-cycle gasoline, diesel, or alternative fuel engine of approximately 10 to 25 horsepower that achieves an hour or more of service per gallon of gasoline. The vehicle **10a** is generally designed for low speed operation and is typically geared to travel no more than approximately 25 miles per hour. Each wheel **13** is chain driven to maximize power, especially at low speed.

Traction steering is often provided to allow the vehicle **10a** to turn in an extremely tight radius that can be nearly within the length of the vehicle **10a**. The traction steering is achieved through a drive system with one or more transmissions that controllably supply power to all of

the wheels 13, or to a track, on one side of the vehicle 10a and separately, controllably provide power to all of the wheels, or to a track, on the other side of the vehicle 10a.

Referring briefly to FIG. 2, which depicts the vehicle dashboard 26a of the platform 11a of FIG. 1, the vehicle 10a includes basic instrumentation such as an oil gage 12, speedometer 14, choke 16, voltmeter 18, ignition switch 20, and headlight switch 22. Steering controls 24 allow an operator to selectively affect the speed to wheels or tracks on one side of the vehicle 10a to effect traction steering.

Referring again to FIG. 1, the all-terrain vehicle 10a has extremely versatile off-road capabilities, including the ability to enter into and climb steep inclines and drive through heavily wooded areas away from dirt roads or trails, and can clear brush and small trees as the vehicle 10a progresses. The vehicle 10a is capable of traversing most off-road terrains where automobiles, all-terrain trucks, or SUV-style vehicles cannot be driven. This includes thick swampland, mud, snow, sand, wooded areas having thick underbrush, ice, grasslands, man-made rubble and debris, uneven ground, inclined surfaces having angles of up to thirty degrees and greater, and floatable operation on water. The vehicle 10a is also capable of freely moving from one terrain to another without modification. This includes the ability to move directly from land to water without requiring in-field modification by an operator. When equipped with tracks, the vehicle 10a has enhanced off-road capabilities and generally exhibits a smoother ride for its operators and passengers.

The vehicle 10a is also capable of floatably operating on waterways regardless of whether the vehicle is equipped with wheels and/or tracks. When operating only with wheels 13, tread ribs 17 on each tire 21 act as oars to propel the vehicle 10a forward across the water. Referring briefly to FIG. 4, tracks 15 can also provide similar forward propulsion on water by being run in reverse.

Floatation capabilities are provided by a lightweight body **19** that may be constructed of a high-density polyethylene or comparable material to further reduce weight. The construction of the body **19** encloses all mechanical components except for the wheels **13**, tires **21**, and tracks **15** and seals against water intrusion to critical engine and transmission parts. The body **19** also provides shielding for most mechanical components from water, mud, sand, rocks, or other objects that the vehicle contacts along the ground or in waterways. In addition to floatation, this shielding also contributes to the capabilities of the vehicle **10a** for traversing difficult terrain and penetrating areas where truck-style vehicles, SUVs and bike-style vehicle cannot operate.

Like the hull of a boat, the body **19** is contoured in shape near the front of the vehicle to optimize on-water handling. As best understood with a comparison of FIGS. 1 and 4, further stability is provided by a symmetrical, generally downwardly tapered cross sectional shape along the length of the body **19**.

Referring again to FIG. 1, while the vehicle **10a** is afloat, the wheels **13** and tires **21** are capable of propelling the vehicle **10a** at speeds of up to about four miles per hour. An optional small marine engine (not shown) can be attached to the rear of the vehicle **10a** to allow for slightly higher speed propulsion. The outboard engine can then be removed and stowed within the vehicle **10a** when the platform **11a** is on land or not in use. However, the outboard engine is not necessary for floatable operation. In many circumstances, water propulsion using the tread ribs **17** of the tires **21** alone may be preferred since the in-field modification of mounting the outboard engine can require an additional amount of time that is not available in an emergency situation. Therefore, in order to permit direct movement from land to water and multiple terrains types, all mechanical components other than wheels, tires and tracks, and the optional outboard marine engine, are carried either internally or on top of the platform **11a**.

The platform is also equipped to protect the passengers from rollovers and external objects. For example, when penetrating thickly wooded areas that include thick underbrush, branches and tall brush, these obstacles are cleared from the path of operators and passengers riding in the vehicle.

5 FIG. 1 depicts a cage **23a** mounted over the vehicle passenger area **75a** of the platform **11a** for protecting passengers from brush and other obstacles. The cage **23a** includes a frame **70a**, roll bar **72a**, brush guard **71a**, and a protective mesh screen **74a**. The roll bar **72a** is constructed of a heavy gauge material to protect passengers in the event that the vehicle **10a** rolls over. The brush guard **71a** comprises multiple brush clearing bars **73a** that are slanted at an angle
10 to extend from about the front of the vehicle **10a** to the top front area of the frame **70a**. Brief reference to FIG. 4 allows a better understanding of the orientation of such clearing bars **73b** with respect to the platform **11b** and the other members of the cage **23a**. During use, the slanted orientation of the brush clearing bars **73b** permits larger branches and other obstacles to be deflected away from passengers.

15 Referring again to the platform **11a** of FIG. 1, the mesh screen **74a**, which extends across the front and at least partially along the sides of the passenger area **75a**, serves to deflect smaller branches and loose external obstacles such as rocks and leaves away from the passengers. The mesh screen **74a** is typically has a steel mesh or expanded metal construction that is sufficient to prevent snapping branches and other debris from coming into contact with a passenger from a
20 head-on or lateral direction. One or more doors **77a** may extend along either side of the cage **23a** to facilitate entry and exit of passengers from the passenger area **75a**. The doors **77a** typically swing open and can be removed when the vehicle **10a** is to be operated in an obstacle-free environment.

The mesh and frame construction of the cage **23a** is usually sufficient to provide each passenger with a relatively unobstructed 360-degree perimeter view around the vehicle **10a**, which can be invaluable for remote navigation or search and rescue uses of the platform **11a**. The heavy gauge material of the cage **23a** can also be steel or another metallic substance that
5 allows the cage **23a** to function as an amplifying antenna to improve the transmission and reception of radio signals by the wireless network technologies of the platform **11a**.

FIG. 4 depicts a number of externally mounted utility devices that can be used to facilitate the in-field command and coordination emergency situations. A public address system **25** is mounted near the front of the vehicle **10b**, and, with brief reference to the view of the
10 dashboard **26b** depicted in FIG. 5, can be operated by an operator in the passenger area **75b** of platform **11a** using a microphone **66b**. The operator can use the public address system **25** to orally relate high-volume instructions to individuals that are located near the platform **11a**. The public address system **25** is of a heavy-duty type well known in the art and is generally capable of withstanding collisions with small objects. Suitable public address systems include the TK-
15 790HBK 9BHS1 VHS High-band Repeating System available from Kenwood interconnected to the Slim Line Speaker, Model SL100\SL100CV (100 Watt) with bumper mount available from Code3, Inc. of St. Louis, Missouri. The TK-790HBK 9BHS1 VHS High-band Repeating System can also be used with the Scorpion 3930 PA System, also available from Code3, Inc. Some embodiments may allow for the megaphone **25** to be integrated into other wireless
20 technologies of the platform **11b** and may allow for remote operation. Referring again to FIG. 4, the brush clearing guards **73b** are positioned to protect the megaphone **25** from collisions with larger objects, such as large branches and small tree trunks, from a head-on collision.

FIG. 4, also depicts an electric winch mounted **79** at about the center front of the vehicle **10b**. The winch **79** is of a type well known in the art to have a capacity of about at least 1,000 to

4,000 lbs. Suitable electric winches include the Superwinch ATV 300 available from Superwinch, Inc., having a capacity of approximately 3000 lbs., and the Power Winch Kit (for Argo) available from Ontario Drive & Gear Limited, having a capacity of approximately 2500 lbs. The winch **79** is generally capable of pulling both personnel and heavy objects from inaccessible locations such as ditches or steep inclines. The winch **79** is also generally capable of pulling the platform **11b** itself from such locations by securing a cable to a fixed and stable position. The cable will usually include a hook or other suitable attachment for connecting to objects such as chains, stretchers, and cleats.

Additional tools may also be included on the platform to perform heavy dragging or pulling operations. As best understood with from FIG. 1, a hitch **81** may also be attached to the rear of the vehicle **10a** to allow for the dragging of a trailer or utility cart. Such trailers may themselves be buoyant to allow for amphibious towing. Some embodiments may allow for additional electronic equipment to be carried in such trailers.

The vehicle **10b** also includes cage-enclosed headlights **81** that are capable of withstanding the impact of small object and debris. The cage-enclosed headlights **81** are located sufficiently behind the brush clearing guards **73** of the platform **11a** so as to be protected from collisions with larger objects such as branches and small tree trunks.

Similar cages and protective covers can also be included to protect other equipment of the platform **11b**. An auxiliary protector **28b** can be added to the cage **23b** to extend protection to one or more fixed components **36b** of an environmental monitoring station **38b**. Referring briefly to FIG. 1, a partial auxiliary protector **28a** can also be used to protect components requiring protection from one or more particular directions. For example, a search light **76** can be a valuable tool for night time driving or for conducting search operations in thickly wooded areas, and is generally controlled from within the vehicle **10a**. The lens and lamp of the search light **76**

may be particularly susceptible to damage from debris coming from a head-on or slightly angled direction. The partial auxiliary protector **28a** specifically provides protection from branches and debris coming from these directions without adding additional unnecessary weight and cost to the platform **11a**. A caged strobe light **78** can also be mounted directly to the frame **70a** or to the
5 brush guard **71a** of the cage **23a**.

In FIG. 4, the fixed components **36b** of the environmental monitoring station **38b** may require a greater degree of protection than a search light **76**. The environmental monitoring station **38b** typically includes a variety of instruments for taking different types of environmental measurements. Examples of such instruments include but are not limited to anemometers and
10 wind vanes, instruments that measure temperature, relative humidity and barometric factors, radiation detectors/Geiger counters, chemical or biological agent sensors, remote heat sensing equipment, and any other device capable of measuring a pertinent environmental condition that is in the vicinity of the platform **11b**. Additional examples are devices capable of measuring dew point, wind chill, heat index, rainfall, wind gusts, cloud base height, and air density.

15 Devices that provide weather station capabilities are well known in the art, such as the WS-2000 wireless weather station by The Science Company, Inc. There is also the IRDAM 4056 by IRDAM, SA., which is a solid state device having no moving parts but which measures wind speed and direction, air temperature, and barometric pressure but not relative humidity or rainfall. It does not calculate dew point or wind chill. However, these data would be easily
20 derivable from the wind speed, relative humidity and temperature, and rainfall collection and measurement would be a relatively simple matter to add.

Instruments that can function from inside the auxiliary protector **28b** of the cage **23b**, such as radiation detectors/Geiger counters, chemical or biological agent sensors, and temperature, relative humidity and barometric measuring devices, may be installed as one or

more of the fixed components **36b** that are positioned within the auxiliary protector **28b**. However, an internally mounted installation could potentially interfere with the operation of an instrument requiring unobstructed exposure to environmental conditions, even if the environmental separation were only through mesh or an expanded metal cage. For example, an anemometer or wind vane would normally require a positioning that would minimize obstructions posed by other components of the platform **11b**, though it is possible that an external mounting of such instruments could make them susceptible to damage from contact with external objects.

Thus, it may be necessary to provide for temporary external mountings of such instruments. FIG. 4 depicts an environmental monitoring station **38b** having an anemometer **40b** and wind vane **42b** mounted on the cage **23a** of the platform **11a** with a detachable stand **27b**. When mounted to the cage **23a** in this manner, the detachable stand **27b** allows the anemometer **40b** and wind vane **42b** to remain in an extended but fixed position with respect to the rest of the platform **11b**. This positioning tends to minimize interference that other components of the platform **11b** may have on relative airflow passing the anemometer **40b** and wind vane **42b**. The detachable stand **27b** is configured for quick and easy mounting and removal from the cage **23a**. In use, the stand **27b**, anemometer **40b** and wind vane **42b** are usually only mounted when the vehicle **10b** is in the field and the platform **11b** is in a stationary position. The stand **27b** is normally disconnected from the cage **23a** and stowed with the anemometer **40b** and wind vane **42b** within the vehicle **10b** when the vehicle **10b** is being driven or when the platform **11b** is not in use. This prevents damage to the anemometer **40b** or wind vane **42b** from contact with obstacles or debris.

FIG. 1 depicts a possible variation on the configuration of the environmental monitoring station **38a** in which a detachable stand **27a** is mounted directly to the vehicle **10a** behind the

vehicle passenger area 75a, the stand 27a extending to a sufficiently vertical position that the attached anemometer 40a and wind vane 42a remain at a mounted position above and behind the cage 23a. The detachable stand 27a is also configured for quick and easy mounting and removal and is normally taken down with the anemometer 40a and wind vane 42a to be stowed either on
5 or within the vehicle 10a when the vehicle 10a is being driven or when the platform 11b is not in use. Other components of the environmental monitoring station 38a mounted behind the vehicle passenger area 75a include a rainwater collection bucket 44, wet bulb thermometer 46, and barometer 48.

FIG. 2 depicts an operator's view of the vehicle dashboard 26a of the platform 11a of
10 FIG. 1, having an example suite of wireless technologies. The environmental monitoring station 38a, depicted in FIG. 1, is configured so that measurements taken by included instruments can be manually or automatically recorded and transmitted to by other devices such as a microprocessor 30a of FIG. 2 or a satellite communication device. Both the microprocessor 30a and, if included, a satellite communication device can be connected to various instruments of the environmental
15 monitoring station 38a of FIG. 1 via a cable 32 so that the output of each instrument can be converted from an electrical signal to a digital or analog signal to be stored and/or visually presented on a dashboard weather display 34. The weather display 34 can include plotting or other data processing facilities and may be incorporated into the microprocessor 30a or be a separate piece of hardware.

20 The wireless technologies of the platform include electronic communication equipment having the capabilities of being moved across each of the multiple types of off-road surfaces that the platform is capable of traversing. The communication equipment includes no fewer than a combined total of two signal transmitters and two signal receivers, though one device often acts as both a receiver and transmitter of at least one type of signal. However, frequently, the

platform will utilize a significantly greater number of transmitters and/or receivers. The platform preferably includes one or more wireless radio transmitters and/or receivers. These radio units are generally configured to operate over several bands and, in order to achieve repetition of systems, it is preferred that at least two separate radio units be incorporated into the platform. A two-way satellite uplink can also be provided in some embodiments, as can optical or visual signal equipment.

Communications equipment depicted on the dashboard 26a of FIG. 1 includes a mobile telephone 60, a transceiver UHF/VHF radio 62, and a transceiver high band/low band radio 64. A microphone 66a is often mounted on the dashboard 26a and configured for use with each of the radios. Suitable mobile telephones, such as cellular and satellite types, are well known in the art and which are available from manufacturers such as Motorola, Qualcomm, and Nokia. Mobile telephones can provide voice communications or, in some embodiments, be used with the microprocessor to provide an additional mode of data communication with remote locations or with the Internet. The radios can also provide voice communications and be used with the microprocessor to provide a mode of data communication with remote locations. One suitable mobile radio is the VX-3000 Mobile available from Land Mobile, a transceiver designed for commercial applications which includes low band, UHF, and VHF and HAM. Various other suitable models are available from manufacturers such as Ericsson/GE, Bendix/King, Vertex, Tait, Maxon, and Mod-U-Con. Other types of radios can also be implemented into the platform 11a.

Additional wireless technologies can include electronic positioning equipment that is capable of providing information about the position of the mobile platform 11a at a given location. In FIG. 2, the platform 11a is equipped with a global positioning system (GPS) 50, of the type that is commonly known in the art, which acts as a receiver of satellite signals for the

electronic computation of position of the platform **11a**. Although the platform **11a** is shown and described in FIG. 2 as using a GPS **50**, it will be appreciated that other types of electronic positioning devices, including loran, radar, sonar, and other wireless systems can also be used and are contemplated to be within the scope of the invention. The GPS **50** or other positioning system may be equipped with a direct data feed to enable coordinate locations or other data to be directly fed into the computer **30a**, the system of the cellular telephone **60**, or the transceiver radios **62** and/or **64** for transmission to a remote location.

Radar, sonar, infrared/thermal imaging and other types of remote sensing systems can also be implemented for both environmental and object sensing. For example, appropriate radar systems can be implemented that allow for weather forecasting and that allow for use in conjunction with other instruments of the weather station. The compilation and processing of data can then be performed with the computer or be passed to a remote location via present wireless technologies. Ground or forest penetrating radar, sonar, and infrared systems can also be used to detect the presence of subterranean objects such as tunnels and land mines and be used for the remote detection of trapped or lost individuals. Suitable ground penetrating radar systems for these purposes include the TerraSIRch SIR-3000 from Geophysical Survey Systems, Inc. (GSSI). Suitable thermal imaging surveillance equipment include the ThermoVision Ranger™ Long Range Surveillance System available from FLIR Systems.

The dashboard **26a**, shown in FIG. 2, can also include visual enhancement equipment such as night vision, infrared devices **82**, or thermal imaging devices which can be mounted or stowed in a dashboard compartment **84** and which can be used by an operator to see at night. The output of the infrared devices **82** or thermal imaging devices may also be displayed on the dashboard **26a** in a small monitor or be configured as goggles worn by one or more of the operators. In the former case, visual image data may be capable of being passed through the

microcomputer 30a or directly to other electronic communications equipment for transmission to a remote location. In the later case, the infrared devices 82 may be capable of being worn by one of the operators when that operator walks away from the platform 11a. Suitable worn night vision devices include the VIPER available from Smart Tech and the ANVIS Dual Generation 3 night vision goggles from Sierra Pacific Infrared. A suitable camera-based system is the IR PRO infrared video camera that is available from Sierra Pacific Infrared.

Digital images may also be recorded, transmitted, and received using a unitary camera and radio transceiver (not shown). In one preferred embodiment, images recorded or received by the radio would also be viewable via a small color monitor on the dashboard 26a and capable of being passed to other devices such as the microprocessor 30a or UHF/VHF and low band/high band radios 62 and 64, or if present, satellite communication equipment, for manipulation by the operator and transmission to remote locations. An example of a suitable unitary camera and radio transceiver would be the VC-H1 Portable Transceiver available from Kenwood.

One or more relay devices are also included among the electronic communication equipment of the platform to allow for the administration, command, and coordination of individuals or sub-units in the field. The relay devices are most often radio-based transceiver repeaters and allow for the receipt and transmission of voice signals from personnel in the field, who are separated by some distance from the platform, to a central remote location. However, the relay devices can also be used to receive and transmit other types of signals, such as environmental data, medical measurements, electronic instructions, or position data between remote personnel and a central location. In some embodiments or situations, the relay devices can also be used to receive and transmit information between separated field personnel or other vehicles or central locations. If necessary, other wireless technologies, such as a radio or wireless

Internet, can also be included among the electronic communication equipment and be configured to perform this relay function.

The rely capabilities of the platform include a crossover ability to receive at least one type of signal that can be regenerated and relayed in at least one different type of signal format.

5 For example, a single radio receiver/transmitter unit can be incorporated that allows for the receipt of a radio signal in a first bandwidth and subsequent amplified (boosted) transmission of the signal in a second bandwidth that is different from the first. Signals received in the second bandwidth can subsequently be re-transmitted in the first bandwidth, allowing the platform to act as a crossover relay for multiple in-field parties having different or incompatible means of
10 communication. Frequently, the platform will be configured to allow for crossover communication across a large number of radio bandwidths and/or between multiple types of devices, such as between mobile telephones, radio transceivers, wireless Internet networks, satellite communication systems, and between other wireless communication formats.

Suitable repeater transceiver devices are well known in the art. A particular repeater
15 transceiver is selected for a particular emergency response platform according to the particular requirements of a frequency ranges in use by emergency response parties and emergency command centers. Suitable repeaters for possible inclusion in the platform of the invention include the TK-690H/790(H)/890(H) radio and repeater units that are available from Kenwood Corporation, each having frequency ranges that vary between about 29.7 MHz and 480 MHz.
20 Other suitable units include the 800 MHz and 900 MHz repeater transceiver units also available from Kenwood Corporation, having ranges varying from about 806 MHz to 940 MHz. The TRP-1000 and ACU-1000 System, available from JPS Communications, Inc., is another suitable crossover frequency repeater that includes two cases that together hold up to ten UHF and VHF radios.

Repeating of video signals is also possible by using an appropriate streaming video system such as the TH-1 "Talking Head" Codec for ISDN & Inmarsat, available from 7E Communications, Ltd. The TH-1 includes a video camera system to allow for image data to be recorded by a platform operator or by remote control and further allows for transmissions to occur via satellite. The TH-1 can be implemented with software that allows for manipulation of image data by an operator using a microprocessor of the platform.

Repeater transceivers can be implemented in various configurations on a platform. FIG. 5 depicts an operator's view of a vehicle dashboard **26b** of the platform **11b** of FIG. 4 having an example suite of wireless technologies. FIG. 6 is a top view of the rear portion of the same platform **11b** of FIG. 4 having the bench seat **54** of the vehicle passenger area **75b** lifted to reveal the boxes of repeater transceivers **52**. The repeater transceivers **52** are interfaced to a laptop-style microprocessor **30b** mounted on the vehicle dashboard **26b** shown in FIG. 5. FIG. 6 also depicts an optional tool box **106** mounted directly behind the vehicle passenger area **75b** and bench seat **54** for storing additional equipment in pull out drawers **107**. Such equipment can include additional repetitive devices such as an additional hand held global positioning unit **108**.

Referring again to FIG. 4, the laptop-style microprocessor **30b** is positioned to allow for in-field operation from the vehicle passenger area **75b** and usually contains interfaces to allow the microprocessor **30b** to be used to control, manipulate, and transfer data between the various electronic communication equipment. The microprocessor **30b** itself is waterproof and is capable of withstanding shocks and functioning in extreme environmental conditions. These attributes allow the microprocessor **30b** to function without damage or lock up as the platform **11b** traverses difficult terrain.

Data contained in the microprocessor **30b** can be recorded, received, transmitted, or relayed between the platform **11b** and remote locations through other wireless communication

systems that are also included on the platform **11b**. The microprocessor **30b** can also incorporate wireless Internet capabilities to allow for the transmission and receipt of data from remote locations. The wireless Internet capability may also utilize one or more of the other transmitters or receivers that are incorporated into the platform **11b** or, in some embodiments, may allow the
5 microprocessor **30b** to operate partially or fully independently of other communication equipment.

One suitable microprocessor is the GoBookMAX laptop computer available from the Itronix Corporation of Spokane, Washington. The software resident on the microprocessor **30b** is usually specifically configured to function as or to work with computer integration software that
10 allows for upwards of 50 different parameter readings from measuring devices such as those of the weather station **38b** or, if present, from positioning equipment of the platform **11b**. Emergency reference software may also be provided, such as the COBRA Emergency Response Software Package available from Defense Group, Inc. (DGI). Additional loaded software on the microprocessor **30b** may include that which is loaded to allow for manipulation of image data
15 gathered by a streaming video system such as the TH-1, when present on the platform **11b**. The microprocessor **30b** can be equipped with built-in or auxiliary positioning equipment, which may be used in conjunction with topographic software loaded in the microprocessor **30b**. An example of such a configuration would be the installation of topographical mapping software such as Topo USA 4.0 (aerial data packet), used in conjunction with an Earthmate™ GPS, both available
20 from the DeLorme Company of Yarmouth, Maine.

The microprocessor **30b** is directly interfaced to a multi-band radio **56** (FIG. 5) and the repeater transceivers **52** (FIG. 6) that are designed to work with the multi-band radio **56**. The combined multi-band radio **56** and repeater transceivers **52** are sufficient to allow for long range broadcasting, repeating, and signal crossover. Programming of selected frequencies for signal

crossover can be performed in-field by an operator via the microprocessor **30b**. This programming can be modified by operators in-field as required by circumstances of a particular emergency situation.

During use at a first remote location in the vicinity of an emergency situation, the
5 repeater transceivers **52** allow for the reception of an incoming signal of a first signal type, for example, a radio signal having any one particular frequency that is programmed by the microprocessor **30b** for repeating. When the incoming signal is received from an in-field emergency response team using a hand held radio, the signal may be relatively weak due to the normal limitations of the response team's smaller broadcasting radio.

10 For example, personal, hand held radio units have frequently been configured to run at 5 watts, giving the units an approximate broadcasting range of 2 miles. While it will be appreciated that actual ranges and equipment specifications will depend on particular equipment, environmental circumstances, and current states of technology, a typical incoming signal of this first signal type could be received and then be regenerated and the signal strength amplified to
15 the approximate scale of 100 watts or more and then be relayed by the repeater transceivers **52** of the platform **11b** as one or more second signal types (eg. different frequencies and/or different types of carrier modulations and bands ranges). Each second signal type would normally be selected by the operator, who would, using the microprocessor **30b**, program the repeater transceivers **52** to receive and re-broadcast transmissions of the second signal type. As a result,
20 transmissions of one or more of the second signal types would also be receivable and be automatically regenerated and relayed as the first signal type. Thus, the platform **11b** would provide crossover broadcasting that would allow different in-field response units with different types of radios to communicate with each other. In addition, operators of the platform **11b** would themselves be able to communicate with different in-field response units or with a remote

centralized command center using the microphone **66b** (FIG. 5) of their own multi-band radio **56** via the transceiver repeaters **52**. If the platform **11b** were to be located in the vicinity of a phone line connection, conventional telephone communications could also be run through the transceiver repeaters **52**.

5 The crossover and repeating operations of the platform **11b** would also permit various in-field response parties to significantly increase the effective range of their communications. For example, a fixed position command center such as a building, a trailer command center, or a command aircraft would characteristically have radio equipment broadcasting at a level on the order of 100 watts, allowing an effective communications range of many tens of miles or more.

10 Although personal communication devices may be able to receive broadcasts from such command centers, they would normally be unable to transmit reply broadcasts due to their limited broadcasting strength. However, the placement of the mobile platform **11b** in the vicinity of the emergency situation would allow for lower power broadcasts from in-field response units to be re-broadcast or repeated at higher powers. For example, referring to FIG. 6, if the repeater

15 transceivers **52** of the mobile platform **11b** are TK-690H/790(H)/890(H) radio and repeater units as described above, the platform **11b** will allow effective broadcasting range to be increased to 30 to 40 miles or more for selected frequency ranges. However, exact numerical ranges are intended to be illustrative only and would depend on specific equipment, circumstances, and current states of technology.

20 Referring now to FIG. 5, even longer range communications are possible with the use of a satellite and/or cellular communications system **58b**, which allows for signals to be relayed from the platform **11b** for transmission by a satellite to a remote location. The satellite communication system **58b** is self-contained in a handset **86** that can be removably inserted in a cradle **68** mounted on the dashboard **26b** of the vehicle **10b**. The satellite communication system

58b is further configured to interface with the microprocessor 30b via a sat-com cord 88 when the handset 86 is inserted in the cradle 68, the interface allowing for all data transfer and radio-based transmissions to be routed through the satellite communication system 58b rather than through the multi-band radio 56 and repeater transceivers 52. When mounted in the cradle, the handset 86 allows for the transmission and reception of satellite signals to be made through an auxiliary antenna 90, shown mounted to the top of the cage 23b in FIG.4. As a satellite uplink, the satellite communication system 58b allows data and voice and/or visual transmissions to be relayed hundreds or thousands of miles away from the vicinity of the emergency situation. The satellite communication system 58b may also have a repetitive, built-in global positioning system.

Due to the self-contained configuration of the handset 86 and the presence of a built-in antenna 92, the satellite communication system 58b can also be removed from the cradle 68 by an operator and be carried away from the platform 11b. The handset 86 retains all functions of the satellite communication system 58b except for the ability to interface with the platform 11b. However, while removed from the cradle 68, the handset 86 can continue to be used as a conventional mobile telephone. While the handset 86 is absent from the cradle 68, all voice/visual and data transmissions and receptions can continue to be passed through the multi-band radio 56 and transceiver repeaters 52 (FIG. 6).

When the handset 86 is returned to the cradle 68, as shown in FIG. 5, the interface between the satellite communication system 58b and microcomputer 30b is restored, allowing satellite voice/visual and data transmissions from the platform 11b to resume. A private line telephone 94 continues to allow the satellite communication system 58b to function as a conventional mobile telephone. Referring briefly to FIG. 6, a connection box 96 connects the private line telephone 94 to the cradle 68 of FIG. 5, allowing passengers to use the mobile

telephone capabilities of the satellite communication system **58b** without removing the handset **86** from the cradle **68** and interfering with the satellite communications interface between the handset **86** and microprocessor **30b**. The connection box **96** also includes a power inverter having standard 12V DC and 110V AC power outlets to allow for the connection and powering
5 of additional electrical devices.

Suitable satellite communications systems include the Globalstar Mobile Satellite Phone and Car Kit available from Qualcomm, Inc. of San Diego, California. Dish-based satellite communication systems, including satellite internet systems, can also be integrated into the platform, and in some embodiments be used in conjunction with other satellite systems. FIG. 7
10 depicts a platform **11c** according to one embodiment of the invention having a mounted dish antenna **98** allowing for high-altitude satellite Internet communications. The mounted dish antenna **98** is used in conjunction with the satellite communication system depicted in FIGS. 4, 5 and 6 and is mounted on the cage **23c** adjacent the auxiliary antenna **90**. The mounted dish antenna **98** may be removable to prevent damage as the vehicle **10c** of the platform **11c** is driven
15 across difficult terrain. Such suitable dish-based satellite communication systems include the Mobile Satellite Unit available from SatCom Solutions.

FIG. 8 depicts a platform **11d** according to one embodiment of the invention having a folding stand-alone dish antenna system **100** positioned on a flatbed **102** that is located behind the cage **23d** of the platform **11d**. The antenna system **100** is capable of collapsing into its case
20 stand **104** for storage during transport. When in use, the antenna system **100** is interfaced to a microprocessor within the platform **11d** and is capable of self-directing its orientation toward to a satellite for uplinking. Suitable stand-alone dish antenna **100** systems include the IPT Suitcase and Fly-Away Systems, both available from SWE-DISH Satellite Systems of Stockholm, Sweden.

The advantages of the invention become apparent in the following hypothetical scenario emergency situation depicted in FIG. 3. Consider an airplane traveling with six passengers, including a pilot, over a relatively inaccessible area 110. The airplane begins to have structural and mechanical problems and begins a downward descent. Before the plane crashes at a crash site 112, the pilot radios his position and indicates that at least one of the passengers has parachuted from the airplane. It is known that the pilot himself was unable to parachute from the plane prior to the crash. It is further known that the airplane lost considerable amounts of fuel prior to crashing, causing a first ground fire 114 in the vicinity of the crash site 112 and a second ground fire 116 near the positions 118 and 120 where passengers landed in parachutes.

The crash site 112, fires 114 and 116, and parachute landing sites 118 and 120 are all located many miles from the nearest dirt path 122. There are no other roads or foot pathways in the area 110. Truck or SUV-style conventional ATVs 124 are dispatched to the area with emergency response parties, each conventional ATV 124 pulling an off-road trailer with emergency response equipment. One ATV 124 pulls a trailer-based command center 126 equipped with high-power communication equipment, administration and medical facilities. The second ATV 124 pulls an off-road flatbed trailer 128 loaded with an emergency response platform 11b of FIG. 4. The dirt path 122 is the closest location to the crash site 112, parachute landing sites 118 and 120, and fires 112 and 116 that the conventional ATVs 124 and off-road trailers 126 can reach, and thus becomes the point of origin for the platform 11b. The trailer-based command center 126 is set up at the end of the dirt path 120.

Emergency response parties are airlifted to locations that are in the vicinity of the crash site 112, parachute landing sites 118 and 120, and fires 112 and 116. Among the parties dispatched are firefighting rescuers 130a-d, paramedics 132a-c, law enforcement 134a-b, and FAA officials 136. Each type of emergency response party is operating on foot and carries at

least one hand held transceiver radio. However, the radios of the firefighting rescuers **130a-d** transceive at a frequency of VHF/LB 155.200 MHz, the radios of the paramedics **132a-c** transceive at UHF 452.600 MHz, the radios of the law enforcement **134a-b** transceive at HB 800MHz, and the radios of the FAA **136** transceive at LB 30.600 MHz.

5 Law enforcement party **134a**, FAA party **136**, firefighting rescuer parties **130a-b**, and paramedic party **132a** are each operating within a general radius **138** surrounding the crash site **112** that is within the broadcasting range of their radios to a summit point **140**. Each are out of broadcasting range of law enforcement party **134b**, firefighting rescuer parties **130c-d**, and paramedic party **132b**, which are operating within a parachute search zone **142**. However, the
10 parachute search zone **142** is mostly within broadcasting range of the summit point **140** for the handheld transceiver radios of each party **134b**, **130c-d**, and **132b**.

Emergency response parties operating equipment that is within range and transceiving at the same frequency will be able to communicate with each other. Consider the first ground fire **114** as firefighting rescuer party **130b** arrives at the scene. It may be that the fire is more severe
15 than originally thought. Firefighting rescuer party **130b** is within the range **138** of firefighting rescuer party **130a** and both parties are transceiving at the same type of signal, radio frequency VHF/LB 155.200 MHz. Firefighting rescuer party **130b** can radio firefighting rescuer party **130a** and request assistance.

Now consider the second fire **116** as firefighting rescuer party **130c** arrives at the scene. It
20 is known that firefighting rescuer party **130d** is also en route to battle the second fire **116**. However, firefighting rescuer party **130c** discovers that the second fire **116** is minor and can be handled without further assistance. Firefighting rescuer party **130c**, operating within range **142** of firefighting rescuer party **130d** at VHF/LB 155.200 MHz, can radio firefighting rescuer party **130d** and instruct the same that the fire is under control and that assistance should be given to

paramedic parties **132b-c** and law enforcement **134b** in the search for the positions **118** and **120** of the parachutes.

Now consider firefighting rescuer party **130d** as it attempts to coordinate its search with paramedic parties **132b-c** and law enforcement **134b**. The firefighting rescuer party **130d** is
5 within broadcasting range of the paramedic parties **132b-c** and law enforcement **134b**, but the radios of the paramedic parties **132b-c** and the law enforcement **134b** operate with second signal types, radio frequencies of UHF 452.600 MHz and HB 800 MHz, respectively. Therefore, the firefighting rescuer party **130d** will not be able to coordinate its efforts without the assistance of a crossover repeater transceiver in the field. Thus, the deployment of the emergency response
10 vehicle **11b** is necessary for the monitoring and coordination of the response to an emergency of this type.

From the dirt path **122**, the emergency response platform **11b** enters a heavily wooded area **144**, traversing rugged, off-trail terrain and thick underbrush. As described with respect to FIG. 4, in order to prevent damage to anemometer **40b** and wind vane **42b**, the detachable stand
15 **27b** will normally be dismounted from the cage **23b** and stowed within the platform **11b**. The cage **23b** protects the operators within the platform **11b** from snapping branches and other objects as the platform **11b** crosses the heavily wooded area **144**.

After penetrating the heavily wooded area **144**, the platform **11b** comes to the edge of a waterway **146** which may be a river that is sufficiently long, wide, and deep to be
20 impassible for normal land-based vehicles. The vehicle **10b** of the platform **11b** simply continues to drive straight into the waterway **146** until the entire platform **11b** begins to float. If the platform **11b** were being driven with wheels **13** and tires **21** only, the operator could simply continue to drive the vehicle **10b** as if it were on land; the tread ribs **17** of the tires **21** would then act as oars and propel the platform **11b** forward across the waterway **146**. However, since tracks

15 have been added wheels 13, the operator reverses the direction of the tracks 15 once the platform 11b begins to float. The tracks 15 then propel the platform 11b forward across the water by being rotated in reverse. The tracks 15 can then be rotated in a forward direction once the platform 11b returns to the opposite bank of the waterway 146. No vehicle modification is
5 required before entering the waterway or after returning to land.

Soon after crossing the waterway 146, the platform 11b encounters a terrain of deep sand dunes 148 and then a steep, muddy incline 150 before reaching the summit point 140. The tracks 15 or, if absent, multiple wheels 13 of the platform 11b provide sufficient traction to enable the vehicle to traverse each of these terrains. Since the operators, equipment, and mechanical
10 components within the platform 11b are protected from water, rocks, and other external objects, the platform 11b arrives at the summit point 140 with little or no damage. Minimal platform set up is required before beginning the administration, command and control of the emergency situation. The summit point 140 is selected as a location for operations since it is a high elevation point and is generally within line of sight of both the radius 138 around the crash site 112 and the
15 parachute search zone 142.

Having radio repeater transceivers 52 included within the platform 11b, the operator uses the microprocessor 30b to program the repeater transceivers 52 to receive incoming signals of a first signal type, in this case radio transmissions from the firefighting rescuer parties 130a-d at VHF/LB 155.200 MHz, and to regenerate and relay (rebroadcast) the signals of second signal
20 types, in this case radio signals having frequencies of UHF 452.600 MHz, HB 800 MHz, and LB 30.600 MHz, receivable by the paramedic, law enforcement, and FAA parties 132a-c, 134a-b, and 136. As part of this crossover programming, the microprocessor 30b is also programmed to receive incoming signals of the second signal types, in this case radio signals having frequencies of UHF 452.600 MHz, HB 800 MHz, and LB 30.600 MHz, and to regenerate and relay the

signals as signals of the first signal type, in this case radio transmissions from the firefighting rescuer parties **130a-d** at VHF/LB 155.200 MHz. Full crossover would also be provided between the UHF 452.600 MHz, HB 800 MHz, and LB 30.600 MHz frequencies to allow the paramedic, law enforcement, and FAA parties **132a-c**, **134a-b**, and **136** to also communicate with each other
5 in the field.

Now consider that, upon arriving at the crash site, the paramedic party **132a** and law enforcement party **134a** learn that two of the six passengers in the airplane **112** are not in the wreckage and have apparently parachuted out of the airplane before the crash. This may be crucial information for response parties in the parachute search zone **142** that are out of hand
10 held broadcast range of the parachute search zone **142**. This may also be important information for operators of a emergency aircraft **152** that, due to the speed of the emergency aircraft **152**, tend to quickly enter and exit the broadcast ranges of any one handheld radio.

Due to its intermediate position on the summit point **140**, the emergency response platform **11b** is capable of serving as a repeater to relay incoming signals of any of the law
15 enforcement, FAA, paramedic, and firefighting rescuer parties **130a-b**, **132a**, **134a**, and **136** of the radius **138** around the crash site to any of the law enforcement, paramedic, and firefighting rescuer parties **130c-d**, **132b**, and **134b** of the parachute search zone **142**. Thus, the platform **11b** can receive an incoming signal of a first signal type, that is any of the selected radio frequencies being utilized by the response parties, from the radius **138** around the crash site **112**, and can
20 regenerate, relay, and possibly amplify the signal as a first or second signal type, that is the same or any other type of selected radio frequency being utilized by the response parties, to the parachute search zone **142**, and vice versa.

The ability of the platform **11b** to move across difficult terrain to reach the intermediate position of the summit point **140** is essential to accomplish this aspect of the invention. Consider

the trailer-based command center 126 located at the nearest dirt path 120. Such command centers will typically have an extensive suite of transceiver, crossover, and repeating equipment for coordinating mobile response activities. This may include equipment operating on the order of 100 watts or more and having the ability to broadcast for many tens of miles or more.

5 Although actual transmission ranges and equipment abilities would depend on specific equipment, circumstances, and current states of technology, respective equipment limitations would limit the ability for previous command centers to exchange signals with in-field parties, making use of the platform 11b advantageous. For example with reference to FIG. 1, the trailer-based command center 126 could have an approximate conventional radio broadcast
10 transmission range limit 127 that extends well beyond both the radius 138 around the crash site 112 and parachute search zone 142. Thus, it may be possible for the trailer-based command center 126 to broadcast signals that are receivable by hand held transceivers of the response parties within the radius 138 of the crash site 112 and parachute search zone 142. However, such broadcasts would be strictly limited to one-way communications since the hand held transceivers
15 would be unable to broadcast back to the trailer-based command center 126 for repeating and/or cross over broadcasting. The same could hold true for communications with an aircraft 152 which could enter and exit hand held broadcast range quickly due to its speed and flight path. The platform therefore provides a repeating and relay utility between response teams and the emergency aircraft 152 and trailer-based command center 126.

20 Now consider that, upon learning that only two passengers successfully parachuted from the airplane, the paramedic and law enforcement response parties 132b-c and 134b in the parachute search zone 142 realize that they have located all of the passengers at their respective landing sites. Meanwhile, firefighter rescuer party 130c radios firefighter rescuer party 130d to report that the second fire 116 has suddenly grown out of control and that further assistance will

be needed. Paramedic parties **132a-c** attend the passengers at their respective positions **118** and **120** and at the crash site **112**.

The environmental monitoring station **38b** (FIG. 7) is used by the operator of the platform **11b** to relay pertinent environmental information such as the wind velocity **154** and temperature, to the firefighter rescuer parties **130a-d**. If the airplane had been carrying hazardous cargo, such as chemical or radioactive substances, sensors on the environmental monitoring station **38b** may be used to detect their presence in the environment as well. Such information could be relayed to a second location such as the trailer-based command center **126** in data files transmitted either by the multi-band radio **56** or via the satellite communication system **58** (both shown in FIG. 5), relayed by a satellite **156**. If signals were to be relayed by the satellite **156**, the signal could be transmitted to a third location hundreds or thousands of miles away from the summit point **140**. Measured environmental data could also be manipulated by the operators of the platform **11b** then relayed, along with appropriate instructions, via radio directly to the response parties in the field. Such information could also be relayed from the platform **11b** to emergency aircraft **152**.

Consider the discovery by paramedic party **132a** that the passenger who parachuted to position **118** has a serious injury and is now a patient who needs prompt expert medical attention before being airlifted. The paramedic party **132a** may know, from its communications with the operators of the platform **11b** and the firefighter rescuer parties **130c-d** that current wind velocity and the fire severity mean that the second fire **116** may shortly threaten their position **118**. If the patient is suffering from apparent radiological, chemical, biological-induced symptoms, the paramedic party **132a** may request that the operators of the platform **11b** consult reference software on their microprocessor **30b** (FIG. 5) containing highly specific information about poison-induced symptoms. The paramedic party **132a** may also rely on expert medical advice

located at the trailer-based command center **126** via relay from the platform **11b**. If the conventional radio-based communication systems of the platform **11b** fail, the platform operators may instead use the satellite communication system to relay voice and data information to the trailer-based command center **126** or to another remote location via the satellite **156**.

5 If the paramedic party **132a** or platform **11b** is equipped with a visual imaging device such as an electronic camera, and if the patient can be possibly transported to a location that is sufficiently close to the visual imaging device to allow for such imaging, image data regarding the patient's condition can also be relayed to the appropriate expert medical authority via satellite.

10 The combination of extreme off-road capabilities, built-in protection to operators and passengers from external obstacles, and integrated communication and environmental monitoring technologies, and unobstructed perimeter views would also make the platform **11b** ideal for use as a tactical assault vehicle. The platform **11b** would be particularly effective for serving in a tactical assault situation where it would be necessary to conduct the administration and
15 coordination of multiple assault parties that each possessed personal communication devices. The above-recited attributes of the invention would also allow the platform **11b** to be useful for the communication or "call-in" of coordinates to appropriate control headquarters for use in the coordination and directing of air strikes against ground targets by both manned and unmanned aircraft.

20 Those skilled in the art will recognize that the various features of this invention described above can be used in various combinations with other elements without departing from the scope of the invention. Thus, the appended claims are intended to be interpreted to cover such equivalent mobile emergency response platforms that do not depart from the spirit and scope of the invention.